

T3 UFH Control Set Accessories

New 230V actuator for control sets U9700040/050

Size	Pcs./Pack	Code
230V 3-point actuator	1	U9750010

Designed specifically for the control sets with motorised mixing valves, the actuator is for 230V operation and is fitted with a 1.5m flexible 3-core cable for convenience.

This actuator allows the use of a separate temperature control system suitable for use with a 3-point actuator. Please see our website (www.emmeti.co.uk) or product pricelist for zone controls, weather compensator codes U9132200 and 210.

The controllers below are also suitable for use with the same control sets as this actuator. Power consumption 5w. Running time 120s. Ambient temperature -5°C – 55°C. Enclosure rating IP41.

New 230V temperature controller for control sets U9700040/050

Size	Pcs./Pack	Code
230V temperature controller c/w sensor	1	U9750021

For mounting directly on the valve in control sets U9700040/050, this integrated temperature controller and actuator with sensor included is designed to regulate mixed water temperature between 5°C and 95°C.

It is a standalone solution, no other input signalling is required. Power consumption 10w. Running time 60s. Ambient temperature -5°C to 55°C. Enclosure rating IP41.

New 230V weather compensating controller for use with control sets U9700040/050

Size	Pcs./Pack	Code
230V weather compensator c/w sensors	1	U9750030

Complete weather compensating controller designed to mount directly on the valves in control sets U9700040/050. Provided with both a water flow temperature sensor and an external sensor with 20m of connecting cable as standard, the controller is designed to regulate mixed water temperature to suit varying weather conditions, by increasing or decreasing the mixed water temperature.

Functionality includes: 24hr/7day programming, pump and boiler control, domestic hot water control, frost protection, PID operation. The unit has a large LCD display to assist both in setting up and in monitoring system status during operation. A pre-wired 1.5m power supply cable is also included. Power consumption 5w. Running time 120s. Ambient temperature 0°C – 40°C. Enclosure rating IP54.

New Replacement motorised mixing valves for use with U9700040

Size	Code
1" 3-way motorised mixing valve kvs 6.3	U9750040
1 1/4" 3-way motorised mixing valve kvs 8	U9750050

The 1" valve is a direct replacement for the valve fitted to U9700040 control set. The 1 1/4" valve is supplied for applications requiring a higher flow rate.