

Price List 2017

TM3 Mixing Unit

TM3 Thermostatic Mixer Control Group with Lowara Ecocirc Class A Pump



Description	Pcs/Pack	Code	Unit Price £
TM3 Control Group,thermostatic mixing valve	1	U1830000	384.70

The TM3 is designed for Underfloor Heating. The control group incorporates a Lowara Ecocirc pump and a mixing valve with remote probe actuation to give a temperature range of between 20 - 70°C, making it suitable for screed drying purposes. It includes a throttle to increase Kv for larger systems. Compatible with our Type 2 Topway manifold 210mm centres. Includes 1" M manifold connections with O-ring seals and 1" M connections for primary flow and return.

Includes a temperature gauge measuring the mixed flow temperature, automatic air vent and bracket to support the weight of the pump.

The Class A pump is ErP 2015 compliant, fixed and variable speed with antiblock technology.

Mixing Valve Kvs 3 - 4.8, 10kw - 18kw.

TM3 Electronic Mixer Control Group with Lowara Ecocirc Class A Pump



Description	Pcs/Pack	Code	Unit Price £
TM3 Control Group, electronic mixing valve	1	U1834000	358.20

The TM3 is designed for Underfloor Heating. The control group incorporates a Lowara Ecocirc pump and a mixing valve suitable for use with an electronic actuator. Compatible with our Type 2 Topway manifold 210mm centres. Includes 1" M manifold connections with O-ring seals and 1" M connections for primary flow and return.

The TM3 includes a temperature gauge measuring the mixed flow temperature, automatic air vent and bracket to support the weight of the pump.

The Class A pump is ErP 2015 compliant, fixed and variable speed with antiblock technology.

Mixing Valve Kvs 4.

The thermostatic mixing valve requires an electronic actuator: 230V 3 point (28157210) or 24V 0-10V (28157220).